



*Illustration purpose

Technical Parameters:

Model	HTH2512UV	
Printing Information		
Printhead	GEN6	
Number of Printheads	2-8 pcs (3-Row)	
Resolution	1200*1200 DPI	
Productivity	Draft Mode	77 m ² /h
	Production Mode	57 m ² /h
	Quality Mode	40 m ² /h
Printing Modes	Bi-directional high speed	
Media & Ink		
Max. Print Width	2.5*1.2 m	
Max. Media Thickness	100 mm	
Media	Finished shoes, bags, toys, handicrafts, home decoration, carving paintings, etc.	
Ink Type	Eco-friendly UV-curable ink (VOC-free)	
Ink Colors	CMYK, Lc, Lm, V, W	
Features		
Curing	LED curing (adjustable power)	
Transfer	USB	
RIP Support	Caldera / Onyx (Optional Purchase)	
Input	PDF, JPEG, TIFF, EPS, AI.....	
Dimensions & Weight		
Printer Dimensions	4670*2510*1380 mm (L*W*H)	
Net Weight	1150 KG	
Gross Weight	1745 KG	
Power & Environment		
Power Consumption	8.3 kW (20A)	
Power Supply	400VAC 50Hz 3L/N/PE	
Environmental Requirements	Independent, clean, low-dust, low-light workspace with good ventilation	
	Operating Temperature: 18°C ~ 30°C (64°F ~ 86°F)	
	Relative Humidity: 30% ~ 70% (non-condensing)	
Others	Requires ADP / Computer	

Industrial Digital Inkjet Comprehensive Solution Provider



Independent printhead-drive technology



Self-developed control system



Self-developed MES system



Independent ink industrial chain



Remote service maintenance system and local services

Shenzhen HandTop Tech Co., Ltd.

www.hanglorygroup.com

Add: Baolong 3rd Road and Gaoke Avenue Intersection, Longgang District, Shenzhen, Guangdong

Tel: (+86)0755-2308 0896

Fax: (+86)0755-2321 7841

E-mail: info@hanglorygroup.com

©Descriptions, illustrations and specifications here of are subject to change without prior notice. Final details shall be subject to contract signed.



V1.0/2025